

Technical Data Sheet

Decorative coating ILLUSION CRISTAL

Ready-made decorative coating

ILLUSION CRISTAL is a smooth decorative coating with a sparkling pearlescent sheen and the addition of a fine fraction of ground glass. Allows you to get a unique surface that changes depending on the direction of the light and creates a shimmering effect.

Properties:

- light dirt is removed from the surface with a wet sponge
- changes shades depending on lighting and angle of view
- depending on the application technique, it allows you to get a variety of patterns

Composition:

Substrate	Water-based synthetic copolymers
Pigment	Pearlescent pigments and glass microspheres
Reducer	Water

Types of substrates:

It is used for interior works as a decorative coating. Apply to a specially prepared surface.

Surface preparation:

The surface must be firm, dry, free of dust, mud, oil and grease. Previously painted surfaces should be cleaned of old flaking material and cleaned with sandpaper. Places affected by mold or moss should be thoroughly cleaned mechanically and treated with D-07 (TM "ELF") primer or other special means.

Performance of works:

Apply tinted DECOR PRIMER to the prepared surface in the required color. Wait until it is completely dry. Stir the material thoroughly before applying and, if necessary, add the dye chosen from the catalog. Apply with a spatula, small or brush, alternating strokes in different directions, creating an original pattern. After 10-15 minutes, lightly smooth the surface with multidirectional movements.

Drying at a temperature of + 20 ° C and a relative humidity of 60%

Touch-dry	12 hours
Complete drying out	24 hours
Recommended temperature conditions	from + 5 °C to + 30 °C

Components

Components

water	30,00%
filler	30,00%
dispersion	35,00%
conserving agent	0,30%
anti-foaming agent	1,00%
auxiliary materials	3,70%

Technical features:

Coverage rate	6 m ² /kg (depending on the application technique)
Non-volatile matter content	40,00%
Solidity	1 kg/l at t=20 ⁰ C
Medium	vinyl copolymer
PH	7,5 - 8,5

Recommendations

Precautions	In case of contact with eyes, rinse immediately with plenty of water.
Storage	In a dry and clean place at a temperature from +5 ⁰ C to + 30 ⁰ C, in a sealed package not less than 12 months from the date of manufacture
Packing	1 kg, 5 kg

ATTENTION:

The firm is not responsible for poor-quality results (the occurrence of coating defects) in case of improper application on inappropriate places and surfaces, at the change of conditions of use, as well as the occurrence of a larger expense at using by not recommended methods