

Technical Data Sheet

Decorative coating TRAVERTINO STYLE Beige, White, Nero

Ready-made decorative coating

TRAVERTINO STYLE is a natural lime coating used for indoor and outdoor works. This material both perfectly transmits the medieval Italian style, and effectively fits into the modern interior. The product creates a firm, wear-resistant and durable coating, and the use of colored waxes creates an additional effect, achieves a variety of color shades and emphasizes the texture. Produced in two bases - WHITE and BEIGE.

Properties:

Resistance to atmospheric precipitation
High strength
Withstands cleaning with alkaline detergents
Antifungal properties
No organic solvents
Environmentally friendly

Composition:

Substrate	Water-emulsion vinyl copolymer
Pigment	Iron oxide pigment
Reducer	Water

Types of substrates:

It is used for interior and exterior works, for decoration of facades. It is also used for decorative finishing of surfaces made of gypsum, cement, lime-cement plaster, brick, concrete and gypsum plasterboard fiber-cement slabs.

Surface preparation:

Decorative coating should be applied only on a quality base. The surface must be firm, dry, free of dust, mud, oil and grease. Previously painted surfaces should be cleaned of old flaking material and cleaned with sandpaper. Places affected by mold or moss should be thoroughly cleaned mechanically and treated with D-07 (TM "ELF") primer or other special means.

Performance of works:

Apply QUARTZ PRIMER or D-17 (TM "ELF") to the prepared surface. Wait until it dries completely. Depending on the substrate, up to 10% of water can be added. Apply 1st layer of material with a stainless steel spatula for the grain size, evenly spreading the product over the entire surface. After the first layer completely dries (8-12 hours), apply the second layer of the material in the same way.

When the second layer dries a little (15-20 minutes), scratch it with a narrow metal spatula, preferably in a horizontal direction, in order to imitate the travertine veins. Before full drying, glaze the surface with a stainless steel spatula. Before applying the decorative layer the priming of the surface with D-14 (TM "ELF") primer is recommended. For creation of the decorative and protective layer inside the premises, it is recommended to use a variety of finishing materials: ANTIQUE, OASIS, DECOR WAX or VINTAGE.

Drying at a temperature of + 20 ° C and a relative humidity of 60%

Touch-dry	12 hours
Complete drying out	24 hours
Recommended temperature conditions	from + 10 °C to + 30 °C

Components

water	15,00%
filler	73,00%
dispersion	10,00%
conserving agent	0,30%
anti-foaming agent	1,00%
auxiliary materials	0,70%

Technical features:

Coverage rate	1,8-2,2 kg/ m ²
Non-volatile matter content	75,00%
Solidity	1,75 kg/l at t=20 ⁰ C
Medium	vinyl copolymer
PH	9,0 — 10,0

Recommendations:

Precautions	In case of contact with eyes, rinse immediately with plenty of water.
Storage	In a dry and clean place at a temperature from +5 ⁰ C to + 30 ⁰ C, in a sealed package not less than 12 months from the date of manufacture
Packing	5 kg, 15 kg

ATTENTION:

The firm is not responsible for poor-quality results (the occurrence of coating defects) in case of improper application on inappropriate places and surfaces, at the change of conditions of use, as well as the occurrence of a larger expense at using by not recommended methods