

## Technical Data Sheet

# Wax emulsion VELATURA Vintage

## Ready-made decorative protective coating

Velatura is a decorative protective coating for interior and exterior works on the basis of the modified siloxane polymers and special auxiliaries, thanks to which the material gains the increased air permeability, water repellency and excellent resistance to harmful environmental factors. Velatura is especially recommended for use as a decorative layer on facades with high vapor permeability.

### Properties:

Water-repellent properties  
Colored with universal colorants  
Does not contain organic solvents  
Environmentally friendly  
Allows to implement complex decoration techniques

### Composition:

Vehicle	Synthetic wax emulsions
Pigment	—
Reducer	Water (up to 20%)

### Types of vehicles:

It is used for interior and exterior works, for decoration of facades. In addition, it can be used as a decorative protective coating for decorative plasters.

### Surface preparation:

Before starting, the surface to be treated should be cleaned of dirt, dried and degreased.

### Performance of works:

Stir well before use.

Depending on the porosity of the surface and the desired effect, water dilution is possible up to 20%.

Apply VELATURA to the prepared surface with a brush or roller and rub with a sponge or a special mitten. The amount of material at application, as well as the degree of its shading, depends on the effect that you want to get. For use on rough porous surfaces, apply the first layer of a non-cured VELATURA base by diluting the product with water for 20%. After drying, apply a second layer, after having colored the product into the required color.

Clean tools with water after use.

### Drying at a temperature of + 20 ° C and a relative humidity of 60%

Touch-dry	1-2 hours
Complete drying out	24 hours
Recommended temperature conditions	Not lower than +10°C

### Componentenets

water	65,00%
filler	-
dispersion	20,00%
conserving agent	0,30%
anti-foaming agent	1,00%
auxiliary materials	13,70%

**Technical features:**

Coverage rate	8-10 m <sup>2</sup> /l
Non-volatile matter content	50,00%
Solidity	1,0 kg/l
Medium	Acrylic copolymer
PH	9

**Recommendations:**

Precautions	In case of contact with eyes, rinse immediately with plenty of water.
Storage	In a dry and clean place at a temperature from +5 °C to + 30°C, in a sealed package not less than 12 months from the date of manufacture
Packing	1 liter, 3 liters

**ATTENTION:**

The firm is not responsible for poor-quality results (the occurrence of coating defects) in case of improper application on inappropriate places